

SF-T520ZS-2E1

Safire Smart

Turret camera 4 in 1 Range E1

2 Mpx (1920x1080) , 1/2.8" CMOS

Starlight

Motorized Lens 2.8~12 mm | IR

Range 50 m

DWDR, HLC, BLC, AGC

Weatherproof IP67



Safire Smart

E1 Professional high quality and performance range

Turret HDTVI, HDCVI, AHD and Analog Camera

CMOS 1/2.8" Starlight

2Mpx (1920x1080)

Output 4in1

2.8~12mm Motorised Lens

0 Lux

IR Range 50 m

3D DNR

IR Cut

Mirror

HLC, BLC, AGC, DWDR

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	E1 High-quality, high-performance professional
Image sensor	1/2.8" CMOS Starlight
Maximum resolution	2 Mpx (1920x1080)
Resolution	2Mpx (25fps)
Lens	Motorized 2.8~12 mm (H): 88.6°~34.4°, V: 57.5°~19.7°, D: 96.47°~39°)
Minimum illumination	0.001 Lux @(F1.2, AGC ON)
Infrared lighting	0 Lux / IR range up to 50 m (ICR)
Day / Night	Auto / Colour / BW (Black and White)
Video output	1 x BNC switchable between HDTVI / HDCVI / AHD / CVBS
Video output switching	Via Switch
Basic functions	OSD menu (remote)
Configurable OSD functions	DWDR, 3D-DNR, AWB, ATW, BLC, AGC, Mirror, Smart IR
Lens Adjustment	3 Axis
Power	DC 12 V / 700 mA, 8.5 W max
Degree of protection	Weatherproof IP67
Temp. operation	-30° C ~ +50° C
Material	Metal body and plastic bracket
Dimensions	99.6 (H) x 111.5 (Ø) mm
Weight	540 g