

SF-T010A-5B1-0360

Safire Smart

Turret camera 4 in 1 Range B1

5 Mpx (2560x1936) , 1/2.5" CMOS

lens 3.6 | IR range 20 m

DWDR, HLC, BLC, AGC

Weatherproof IP67



Safire Smart

Range B1 Economical

Turret HDTVI, HDCVI, AHD and Analog Camera
CMOS 1/2.5"

5Mpx (2560x1936)

Output 4in1

3.6mm lens

0 Lux

IR Range 20 m

2D DNR

IR Cut

Mirror

HLC, BLC, AGC, DWDR

Built-in microphone, audio over coaxial

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1 Economic
Image sensor	1/2.5" CMOS
Maximum resolution	5 Mpx (2560x1936)
Resolution	5MP@20fps /4MP@30fps
Lens	3.6 mm (H: 88.6°, V: 72.4°, D: 101.3°)
Minimum illumination	0.01 Lux @(F1.2, AGC ON)
Infrared lighting	0 Lux / IR range up to 20 m (ICR)
Day / Night	Auto / Colour / BW (Black and White)
Video output	1 x BNC switchable between HDTVI / HDCVI / AHD / CVBS
Video output switching	Via Switch
Audio	Built-in microphone, audio over coaxial
Basic functions	OSD menu (remote)
Configurable OSD functions	DWDR, 2D-DNR, AWB, ATW, BLC, AGC, Mirror, Smart IR
Lens Adjustment	3 Axis
Power	DC 12 V / 250 mA, 3W max
Degree of protection	Weatherproof IP67
Temp. operation	-30° C ~ +50° C
Material	Metal body and plastic bracket
Dimensions	82.8 (H) x 94.8 (Ø) mm
Weight	200 g